

# ECOLOGY 2500LT

*Constant pressure thermoplastic hose for medium pressure lateral sewer cleaning applications up to 175 bar*



## INNER TUBE

Polyester elastomer

## REINFORCEMENT

One braid of synthetic fiber

## COVER

Polyurethane - black - pinpricked - white inkjet branding

## APPLICATIONS

Compact sewer cleaning vehicles and equipment for cleaning smaller residential and commercial lines

## FEATURES

Abrasion resistant - Compact - Lightweight and extremely flexible - Kink resistant - Polyester braid design - Black cover resistant to humid working conditions to increase lifetime

## TEMPERATURE RANGE

-40 °C to 60 °C (-40 °F to 140 °F)

## DESCRIPTION

Hose suitable for lateral cleaning applications requiring medium high pressure performance and high flexibility for cleaning the smaller sewer pipes. Also available as factory made assemblies: please contact our sales office for further details

## TECHNICAL DATA

Part no.	ID	OD	Working Pressure	Bursting Pressure	Bend Radius	Weight
5913.00	3/16" DN5	8,5 mm	175 bar	440 bar	25 mm	45 g/m
5914.00	1/4" DN6	10,60 mm	175 bar	440 bar	40 mm	65 g/m

## AVAILABLE LENGTHS

10/15/20 mt, more options available upon request.

## FITTINGS

Reel side: 1/4" F swivel, 1/2" M, 1/2" F

Nozzle side: directly at the hose (A), 1/8" M (B), 1/4" M (C).

  
nuova**Contec**  
[www.nuovacontec.com](http://www.nuovacontec.com)

