

INSERTS FOR HP NOZZLES

WITH WORKING PRESSURE UP TO 1500 BAR



Made of hardened and polished SS, they are fitted with a flow straightener that grants for a very linear and efficient HP jet. The APF4 inserts are suitable to be flush mounted on the head of the nozzle.

APPLICATIONS:

- AP2 inserts: Warthog, Spitfire, Badger, Gopher, Raptor series.
- AP4/APF4 inserts: Raptor, BJV, Torus, nozzle series and selfrotary heads.

The flow straighteners are installed on most inserts.

Orifice Size		INSERTS 1/8" NPT	INSERTS 1/4" NPT	
mm	inches	AP2	AP4	APF4
0,46	0,018	ST.AP2018	ST.AP4018	ST.APF4018
0,51	0,020	ST.AP2020	ST.AP4020	ST.APF4020
0,56	0,022	ST.AP2022	ST.AP4022	ST.APF4022
0,61	0,024	ST.AP2024	ST.AP4024	ST.APF4024
0,66	0,026	ST.AP2026	ST.AP4026	ST.APF4026
0,74	0,029	ST.AP2029	ST.AP4029	ST.APF4029
0,81	0,032	ST.AP2032	ST.AP4032	ST.APF4032
0,89	0,035	ST.AP2035	ST.AP4035	ST.APF4035
0,97	0,038	ST.AP2038	ST.AP4038	ST.APF4038
1,07	0,042	ST.AP2042	ST.AP4042	ST.APF4042
1,19	0,047		ST.AP4047	ST.APF4047
1,32	0,052	ST.AP2052	ST.AP4052	ST.APF4052
1,45	0,057	ST.AP2057	ST.AP4057	ST.APF4057
1,60	0,063	ST.AP2063	ST.AP4063	ST.APF4063
1,75	0,069	ST.AP2069	ST.AP4069	ST.APF4069
1,91	0,075	ST.AP2075	ST.AP4075	ST.APF4075
2,08	0,082	ST.AP2082	ST.AP4082	ST.APF4082
2,29	0,090	ST.AP2090	ST.AP4090	ST.APF4090
2,49	0,098	ST.AP2098	ST.AP4098	ST.APF4098
2,69	0,106	ST.AP2106	ST.AP4106	ST.APF4106
2,92	0,115	ST.AP2115	ST.AP4115	ST.APF4115
3,18	0,125	ST.AP2125	ST.AP4125	ST.APF4125
3,43	0,135	ST.AP2135	ST.AP4135	ST.APF4135
3,68	0,145		ST.AP4145	ST.APF4145
3,94	0,155		ST.AP4155	ST.APF4155
4,19	0,165		ST.AP4165	ST.APF4165



85500.503
3/8" Socket Wrench



85500.504
9/16" Socket Wrench



85500.503
3/8" Socket Wrench