

R7 ANTIABRASION

Thermoplastic hose MSHA approved for hydraulic applications from 70 to 210 bar

ORDERING INFORMATION

1/4" HOSES FITTED	A	B	C
<i>Lengths / fitting reel side</i>	<i>Part numbers</i>		
10 mt fitted:			
1/4"F	5917.10A	5917.10B	5917.10C
1/2"M	5917.10A.2M	5917.10B.2M	5917.10C.2M
1/2"F	5917.10A.2F	5917.10B.2F	5917.10C.2F
15 mt con raccordo:			
1/4"F	5917.15A	5917.15B	5917.15C
1/2"M	5917.15A.2M	5917.15B.2M	5917.15C.2M
1/2"F	5917.15A.2F	5917.15B.2F	5917.15C.2F
20 mt con raccordo:			
1/4"F	5917.20A	5917.20B	5917.20C
1/2"M	5917.20A.2M	5917.20B.2M	5917.20C.2M
1/2"F	5917.20A.2F	5917.20B.2F	5917.20C.2F

CONNECTION WITH THE NOZZLES

A: directly at the hose;

B: 1/8"M;

C: 1/4"M.

FITTINGS AND FERRULES

<i>Description</i>	<i>Part numbers</i>
Nozzle w/hose fitting	5500.012
Nozzle w/hose fitting w/frontal jet	5500.012A
1/8" M thread w/hose fitting	5911.05B
1/4"M thread w/hose fitting	5911.055
1/4"F thread w/hose fitting	4105.01F
1/2"M thread w/hose fitting	4105.05M
1/2"F thread w/hose fitting	4105.05F
Short ferrule	5912.06C
Standard ferrule	5912.06

