

## Technical data

	Usage	B. R. (mm)	W. P. (bar)	B. P. (bar)	Vacuum (bar)	Weight (kg/m)	Thick- ness (mm)	Material	Coil Length (m)	Part number(*)
<b>DN 80</b>										
<b>ARIZONA</b>	Sewers and septic tanks	320	3,5	10,5	0,9	1,85	6,3	PVC	30/50	<b>2020.80-xx</b>
<b>APOLLO SE</b>	Sewers and septic tanks	320	3	9,0	1,0	1,82	5,1 - 6	PVC	50	<b>2031.80-xx</b>
<b>APOLLO SUPERFLEX 2</b>	Sewers and septic tanks	270	1,5	7,5	0,7	1,9	5,1 - 6,4	PVC/NBR	50	<b>2032.80-xx</b>
<b>APDATEC 144</b>	Sewers and septic tanks	250	3		0,9	1,95	6	PVC/buna	30/50	<b>2016.080-xx</b>
<b>MARTE</b>	Mineral oil, lubricants	460	5	15	1,0	2,21	6,6	PVC	50	<b>2033.80-xx</b>
<b>ASPIVRAC-S</b>	Industrial applications	160	1,5	4,5	0,8	3,16	8	NR rubber	20	<b>2009.80-xx</b>
<b>DN 100/102</b>										
<b>ARIZONA</b>	Sewers and septic tanks	400	3	9,0	0,9	2,7	7,3	PVC	30/50	<b>2020.100-xx</b>
<b>APOLLO SE</b>	Sewers and septic tanks	410	3	9,0	0,85	2,66	6 - 7,0	PVC	30	<b>2031.100-xx</b>
<b>APOLLO SUPERFLEX 2</b>	Sewers and septic tanks	335	1,5	6,0	0,6	2,75	5,9 - 7,2	PVC/NBR	50	<b>2032.102-xx</b>
<b>APDATEC 144</b>	Sewers and septic tanks	320	3		0,9	2,7	6,5	PVC/buna	30/50	<b>2016.100-xx</b>
<b>MARTE</b>	Mineral oil, lubricants	600	4	12	1,0	3,37	7,1	PVC	30	<b>2033.102-xx</b>
<b>ASPIVRAC-S</b>	Industrial applications	200	1,5	4,5	0,8	3,8	8	NR rubber	10/20	<b>2009.100-xx</b>

## Fields of application

Applications Hose	Sewer cleaning and septic tanks	Liquids	Use at low temperatures	Hydrocarbons	Debris heavy	Powders abrasive	Proboscis
<b>ARIZONA</b>	•	•					
<b>APOLLO SE</b>		•					
<b>APOLLO SUPERFLEX 2</b>	•	•	•				
<b>APDATEC 144</b>	•	•	•				
<b>MARTE</b>				•			
<b>ASPIVRAC-S</b>						•	•

(\*) xx: coil length in mt

**B.R.:** Bending Radius**W.P.:** Working Pressure**B.P.:** Bursting Pressure