

# TOIVAC-N

## Features

Hose with smooth inner surface to optimise flow, suitable for sanitary suction, duct cleaning, sewer inspection. Rugged yet lightweight and flexible even at low temperatures.

Can be supplied complete with seal-welded sleeves + 7.5m of black PPM rope on request.

**Colour:** yellow and black

**Working Temperature:** - 40°C + 60°C

**Features:** Polyethylene tubing with constant wall thickness of 1.4mm

## Applications

Designed for sanitary suction, duct cleaning, sewer inspections



| Part num. | DN (mm) | T. (mm) | W (g/m) | B.R. (mm) | V. (bar) | C.L. (m)     |
|-----------|---------|---------|---------|-----------|----------|--------------|
| 2017.051  | 51      | 1,4     | 950     | 85        | 0,95     | 7,5/10/15/20 |
| 2017.063  | 63      | 1,4     | 1150    | 105       | 0,95     | 7,5/10/15/20 |
| 2017.076  | 76      | 1,4     | 1400    | 126       | 0,95     | 7,5/10/15/20 |
| 2017.102  | 102     | 1,4     | 1800    | 165       | 0,85     | 7,5/10/15/20 |

## Legend

- **T.:** Thickness
- **W.:** Weight
- **B.R.:** Bending Radius
- **V.:** Vacuum
- **C.L.:** Coil length