

DESCRIPTION

Light Standard Nozzles with conical head.

MAIN FEATURES

Conical-head nozzles with interchangeable M6 steel inserts and rear jets with 20° inclination. Available with front hole upon request.









RECOMMENDATIONS

For effective and efficient operation, the nozzles must be specially configured (with regard to the size of individual holes), depending on the characteristics of the pump (flow rate and pressure) and the cross-section, length and type of high-pressure hose. This information must be provided by the customer at the time of order and must be compatible with the technical specifications of each individual nozzle.

The operator must choose a working pressure compatible with the pipeline conditions: high working pressure values could cause structural damage to the pipe walls.

Maximum Pressure: 300 bar

TECHNICAL SPECIFICATIONS

Art. Nr.		Ø x L								Inserts
		mm	kg					lit/min	mm	
5515.300	1/2"	42 x 51	0,25	6 x M6	20°	1 x M6	0°	40 - 170	50 - 200	Steel
5515.300C	1/2"	42 x 51	0,25	6 x M6	20°	1 x M6	0°	40 - 170	50 - 200	Ceramic
5515.600	3/4"	49 x 58	0,34	6 x M6	20°	1 x M6	0°	50 - 230	100 - 250	Steel
5515.600C	3/4"	49 x 58	0,34	6 x M6	20°	1 x M6	0°	50 - 230	100 - 250	Ceramic
5515.700	1"	58 x 69	0,5	6 x M6	20°	1 x M6	0°	50 - 260	100 - 300	Steel
5515.700C	1"	58 x 69	0,5	6 x M6	20°	1 x M6	0°	50 - 260	100 - 300	Ceramic